



Shanghai Lunsure Electronic  
Technology Co.,Ltd  
Tel:0086-21-37185008  
Fax:0086-21-57152769

# MC7815

## Three-Terminal Positive Voltage Regulators

### Features

- Output current in excess of 1.0 Ampere
- No external components required
- Internal thermal overload protection
- Internal short-circuit current limiting
- Output voltage offered in 2% tolerance


### Maximum Ratings @ $T_A=25^\circ\text{C}$ , Unless Otherwise Noted

Parameter	Symbol	Value	Unit
Input Voltage	$V_1$	30	V
Operating Ambient Temperature	$P_D$	15	W
Operating Junction Temperature	$T_{OPR}$	-20---+75	$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55---+125	$^\circ\text{C}$

### Electrical Characteristics ( $V_i=23\text{V}$ , $I_o=500\text{mA}$ , $0^\circ\text{C}<T_j<125^\circ\text{C}$ , $C_i=0.33\mu\text{F}$ , $C_o=0.1\mu\text{F}$ , Unless Otherwise Specified)

Parameter	Sym	Min	Typ	Max	Test conditions
Output Voltage	$V_o$	14.7V	15.0V	15.3V	$T_j=25^\circ\text{C}$
		14.55V		15.45V	$17.5\text{V} \leq V_1 \leq 30\text{V}$ , $5\text{mA} \leq I_o \leq 1.0\text{A}$ , $P_D=15\text{W}$
Load Regulation	$\Delta V_o$		12mV	300mV	$5\text{mA} \leq I_o \leq 1.5\text{A}$ , $T_j=25^\circ\text{C}$ ,
			4.0mV	150mV	$250\text{mA} \leq I_o \leq 750\text{mA}$ , $T_j=25^\circ\text{C}$
Line regulation	$\Delta V_o$		11mV	300mV	$17.5\text{V} \leq V_1 \leq 30\text{V}$ , $T_j=25^\circ\text{C}$
			3.0mV	150mV	$16\text{V} \leq V_1 \leq 22\text{V}$ , $T_j=25^\circ\text{C}$
Quiescent Current	$I_q$		4.4mA	8.0mA	$T_j=25^\circ\text{C}$ , $I_o=0$
Quiescent Current Change	$\Delta I_q$			1.0mA 0.5mA	$14.5\text{V} \leq V_1 \leq 30\text{V}$ $5\text{mA} \leq I_o \leq 1.0\text{A}$
Output Noise Voltage	$V_N$		90 $\mu\text{V}$		$10\text{Hz} \leq f \leq 100\text{KHz}$ $T_j=25^\circ\text{C}$
Ripple Rejection	RR	55dB	70dB		$f=120\text{Hz}$
Dropout Voltage	$V_d$		2.0V		$I_o=1.0\text{A}$ , $T_j=25^\circ\text{C}$
Output Short Circuit Current	$R_o$		19mohm		$f=1.0\text{KHz}$
Output Short Circuit Current	$I_{os}$		230mA		$T_j=25^\circ\text{C}$
Peak Output Current	$I_{opeak}$		2.1A		$T_j=25^\circ\text{C}$
Temperature Coefficient of Output voltage	$\frac{\Delta V_o}{\Delta T_j}$		1.0mV/ $^\circ\text{C}$		$0^\circ\text{C} \leq T_j \leq 125^\circ\text{C}$ , $I_o=5\text{mA}$

### TO-220



#### DIMENSIONS

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.560	.625	14.22	15.88	
B	.380	.420	9.65	10.67	
C	.100	.135	2.54	3.43	
D	.230	.270	5.84	6.86	
E	.380	.420	9.65	10.67	
F	-----	.250	-----	6.35	
G	.500	.580	12.70	14.73	
H	.090	.110	2.29	2.79	
I	.020	.045	0.51	1.14	
J	.012	.025	0.30	0.64	
K	.139	.161	3.53	4.09	∅
L	.140	.190	3.56	4.83	
M	.045	.055	1.14	1.40	
N	.080	.115	2.03	2.92	

MC7815



Representation Schematic Diagram

